

## APPLICATION

The Fakro DWF60 Knee Wall Access Door sets a new standard in fire safety and thermal efficiency. Designed to provide access to unused spaces behind low partition walls, this model ensures 60 minutes of fire resistance (EI1/EI2=60 as per EN13501-2) and enhanced thermal insulation with an R-value of 12. Its upgraded construction and features make it a superior choice for both safety and functionality.

## FEATURES

- Fire-resistant for 60 minutes (EI1/EI2=60 as per EN13501-2)
- Enhanced R-value of 12 for superior thermal insulation
- 3-3/8 in. thick insulated door panel finished in white on both sides
- Triple seal system: includes perimeter rubber seal, intumescent fire seal, and additional perimeter seal for improved airtightness
- Features a removable handle for secure closure
- Universal installation with left or right swing options
- Includes 1-3/8 in. wide natural wood trim kit (unpainted)
- 3-year warranty

## SPECIFICATIONS

**DOOR:**  
Insulated with fire-proof material, 2½"  
Thermal insulation thickness: 2¾"  
Finished on both sides with white  
HDF board.

**FRAME:**  
Made of pinewood.  
Depth (Jamb): 3½"  
Equipped with a seal.

**EQUIPMENT:**  
Handle with a lock to ensure tight  
closing.  
1¾ wide wooden finishing slats in  
natural colour.

For a complete list of options visit  
[www.AccessDoorsAndPanels.com](http://www.AccessDoorsAndPanels.com)

## SKU: DWF-FIRERATED-27-35

# KNEE WALL ACCESS DOOR

### FIRE-RATED



## DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

### SIZES:

No.	Size
1	21 x 31
2	27 x 35

### TECHNICAL PARAMETERS:

No.	Description	Value	Standard
1	Door heat transfer coefficient	U = 0.11 BTU/hft²F	PN-EN 10211:2008
2	Tightness	4th class*	EN 12207
3	Fire resistance (on both sides)	EI,45	EN 13501-2

\* Manufacturer's internal calculations

### ASSEMBLY INFORMATION

DWF knee wall door comes pre assembled and must be installed in framed rough opening in accordance with the included fitting instructions. One must ensure that the gap between door frame and rough opening framing is properly insulated.



Twist lock handle



White finish  
(paintable)



Concealed  
insulation of 3 1/8"



Thermal gasket  
(expands in high  
temperatures)



### RECOMMENDED FOR:

- Garage to pantry access
- Storage access
- Crawl space access
- Under stair space access
- Attic closet



Universal fit  
(left or right swing)



2 Weather seal gaskets



Trim kit included



120° Opening up to 120°

## PROJECT DATA

Custom Sizes Available - Fast!

Scan  or  Click



To view Pricing and  
Additional Product Info.

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			



TELEPHONE:  
1-888-457-1275  
FAX:  
1-888-626-2907



PO BOX 66738 #76520,  
SAINT LOUIS, MO  
63166-6738  
USA



WEBSITE:  
[www.AccessDoorsAndPanels.com](http://www.AccessDoorsAndPanels.com)  
E-MAIL:  
[info@AccessDoorsAndPanels.com](mailto:info@AccessDoorsAndPanels.com)



# DWF-FIRERATED- 27-35

# FIRE-RATED KNEE WALL ACCESS DOOR

Dimension W x H		21 x 31	27 x 35
Rough opening [in.]	A x B	21½ x 31¼	27½ x 35¼
Frame external dimensions [in.]	W x L	21 x 31	27 x 35
Frame internal dimensions [in.]	M x N	19 x 28¾	24¾ x 32¾
Frame depth [in.]	S	3½	
Frame thickness[in.]	Z	1	

