

SUBMITTAL/TECHNICAL DATA SHEET



DESCRIPTION

This fire-rated Upward Opening Access Door is designed for those special ceiling applications when the door must swing upward into the ceiling cavity.

FEATURES

- Fire-Rated
- Self-Closing by Gravity
- Ceiling Installation
- Custom Sizing

SPECIFICATIONS

MODEL: BFRU

DOOR: 18 gauge Steel

FRAME: 16 gauge Steel

SIZE:
Min: > 24 inches by 36 inches
Max: 40 inches by 70 inches

INSTALLATION: Ceiling

FLANGE: 1 inch Exposed

HINGE: Concealed Continuous Piano

LATCH: 1/4 inch Allen Head Key

INSULATION: 1½ inch fire-rated insulation, R-6.3

FINISH: Off White Prime Coat

WARRANTY: 1 year

OPTIONS: Materials and Gaskets

CERTIFICATION:
Warnock-Hersey listed for 2 hours



SKU: **FBRU**

**FIRE-RATED UPWARD
OPENING ACCESS DOOR**



DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

STANDARD SIZES:

WIDTH x HEIGHT	
24 x 48	30 x 48
30 x 30	32 x 32
30 x 36	36 x 36

Custom sizes are available. Use IUA for access doors 24 x 36 or smaller.
Rough opening is door size + 1/4.

OPTIONS:

G - Gasketing	S - T304 Stainless Steel
B - Bonderized/Galvanized	



For a complete list of options visit
www.AccessDoorsAndPanels.com

PROJECT DATA

Custom Sizes Available - Fast!

Scan or Click



To view Pricing and
Additional Product Info.

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			

TELEPHONE:
1-888-457-1275
FAX:
1-888-626-2907



PO BOX 66738 #76520,
SAINT LOUIS, MO
63166-6738
USA



WEBSITE:
www.AccessDoorsAndPanels.com
E-MAIL:
info@accessdoorsandpanels.com