

SUBMITTAL/TECHNICAL DATA SHEET



DESCRIPTION

This fire-rated Upward Opening Access Door is designed for those special ceiling applications when the door must swing upward into the ceiling cavity.

FEATURES

- Fire-Rated
- Self-Closing by Gravity
- Ceiling Installation
- Custom Sizing

SPECIFICATIONS

MODEL: BFRU

DOOR: 18 gauge Steel

FRAME: 16 gauge Steel

SIZE:
Min: > 24 inches by 36 inches
Max: 40 inches by 70 inches

INSTALLATION: Ceiling

FLANGE: 1 inch Exposed

HINGE: Concealed Continuous Piano

LATCH: 1/4 inch Allen Head Key

INSULATION: 1 1/2 inch fire-rated insulation,
R-6.3

FINISH: Off White Prime Coat

WARRANTY: 1 year

OPTIONS: Materials and Gaskets

CERTIFICATION:
Warnock-Hersey listed for 2 hours

SKU: **FBHS**

FIRE-RATED UPWARD OPENING ACCESS DOOR



DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

STANDARD SIZES:

WIDTH x HEIGHT	
12 x 12	22 x 30
16 x 16	24 x 24
18 x 18	24 x 36*
24 x 40*	24 x 48*

Custom sizes are available.
Rough opening is door size + 3/4.
Recommended for vertical surfaces only.

OPTIONS:

LATCH	Topics
D - Detention lock prep	G - Gasketing
M - Mortise lock (1-1/8) prep	M - Masonry Anchors
S - Security screws	S - T304 Security Steel

For a complete list of options visit
www.AccessDoorsAndPanels.com

PROJECT DATA

Custom Sizes Available - Fast!

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			

Scan  or  Click



To view Pricing and
Additional Product Info.



TELEPHONE:
1-888-457-1275
FAX:
1-888-626-2907



PO BOX 66738 #76520,
SAINT LOUIS, MO
63166-6738
USA



WEBSITE:
www.AccessDoorsAndPanels.com
E-MAIL:
info@accessdoorsandpanels.com