

SUBMITTAL/TECHNICAL DATA SHEET



SPECIFICATIONS

DOOR: 20 gauge cold rolled steel

FRAME: 16 gauge cold rolled steel

HINGE: Concealed Pin

FINISH: Gray powder paint

INSULATION: 2 thick fire rated mineral fiber

CERTIFICATION:

UL listed B label for 1-1/2hrs (vertical)

Warnock-Hersey listed for 3 hrs (horizontal)

SKU: **FBIP**

FIRE-RATED UPWARD OPENING ACCESS DOOR



DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

STANDARD SIZES:

WIDTH x HEIGHT			
8 x 8	16 x 16	22 x 36	32 x 32*
10 x 10	18 x 18	24 x 24	36 x 36*
12 x 12	18 x 24	24 x 30	36 x 48*
12 x 18	20 x 30	24 x 36	48 x 48*
12 x 24	22 x 22	24 x 48*	
14 x 14	22 x 30	30 x 30*	

Custom sizes are available.
Rough opening is door size + 1/4.

*Vertical application only.

OPTIONS:

FLANGE	LATCH	OPTIONAL
T - 1 Flange	K - Knurled knob/key operated latch bolt	B - Bonderized / galvanized
W - Drywall bead		G - Gasketing
P - Plaster casing	M - Mortise lock (1-1/8) prep	M - Masonry anchors
		S - T304 Stainless steel



For a complete list of options visit
www.AccessDoorsAndPanels.com

PROJECT DATA

Custom Sizes Available - Fast!

Scan  or  Click



To view Pricing and
Additional Product Info.

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			



TELEPHONE:
1-888-457-1275
FAX:
1-888-626-2907



PO BOX 66738 #76520,
SAINT LOUIS, MO
63166-6738
USA



WEBSITE:
www.AccessDoorsAndPanels.com
E-MAIL:
info@accessdoorsandpanels.com