

SUBMITTAL/TECHNICAL DATA SHEET



SPECIFICATIONS

- DOOR:**
14 gauge cold rolled steel
- FRAME:**
14 gauge cold rolled steel
- HINGE:**
Concealed pin
- FINISH:**
Gray powder paint
- INSULATION:**
2 thick fire rated mineral fiber
- CERTIFICATION:**
UL listed B label for 1-1/2 hrs



SKU: **FBSP**

**FIRE-RATED SECURITY
ACCESS DOOR**



DIMENSIONS AND APPEARANCE

>> [CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<](#)

STANDARD SIZES:

WIDTH x HEIGHT	
12 x 12	24 x 24
16 x 16	24 x 36
18 x 18	24 x 40
22 x 30	24 x 48

Custom sizes are available. Rough opening is door size + 1/4.

OPTIONS:

FLANGE	LATCH	OPTIONAL
T - 1 Flange	K - Knurled knob/key operated latch bolt	B - Bonderized / galvanized
W - Drywall bead		G - Gasketing
P - Plaster casing	M - Mortise lock (1-1/8) prep	M - Masonry anchors
		S - T304 Stainless Steel



For a complete list of options visit www.AccessDoorsAndPanels.com

PROJECT DATA

Custom Sizes Available - Fast!

Scan or Click



To view Pricing and Additional Product Info.

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :	SUBMITTAL APPROVAL : (signature or stamp)			
TAGGING INSTRUCTIONS :				

TELEPHONE:
1-888-457-1275

FAX:
1-888-626-2907



PO BOX 66738 #76520,
SAINT LOUIS, MO
63166-6738
USA



WEBSITE:
www.AccessDoorsAndPanels.com

E-MAIL:
info@accessdoorsandpanels.com