

# SUBMITTAL/TECHNICAL DATA SHEET



## SPECIFICATIONS

- DOOR:**  
14 gauge cold rolled steel
- FRAME:**  
14 gauge cold rolled steel
- HINGE:**  
Concealed pin
- FINISH:**  
Gray powder paint
- INSULATION:**  
2 thick fire rated mineral fiber
- CERTIFICATION:**  
UL listed B label for 1-1/2 hrs



SKU: **FBSW**

**FIRE-RATED SECURITY  
ACCESS DOOR**



## ■ DIMENSIONS AND APPEARANCE

>> [CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<](#)

### STANDARD SIZES:

WIDTH x HEIGHT	
12 x 12	24 x 24
16 x 16	24 x 36
18 x 18	24 x 40
22 x 30	24 x 48

Custom sizes are available. Rough opening is door size + 1/4.

### OPTIONS:


FLANGE	LATCH	OPTIONAL
T - 1 Flange	K - Knurled knob/key operated latch bolt	B - Bonderized / galvanized
W - Drywall bead		G - Gasketing
P - Plaster casing	M - Mortise lock (1-1/8) prep	M - Masonry anchors
		S - T304 Stainless Steel



For a complete list of options visit [www.AccessDoorsAndPanels.com](http://www.AccessDoorsAndPanels.com)

## ■ PROJECT DATA

**Custom Sizes Available - Fast!**

Scan  or  Click



To view Pricing and Additional Product Info.

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			

TELEPHONE:  
1-888-457-1275

FAX:  
1-888-626-2907



PO BOX 66738 #76520,  
SAINT LOUIS, MO  
63166-6738  
USA



WEBSITE:  
[www.AccessDoorsAndPanels.com](http://www.AccessDoorsAndPanels.com)

E-MAIL:  
[info@accessdoorsandpanels.com](mailto:info@accessdoorsandpanels.com)