

## DESCRIPTIONS

The Standard Fixed Curb-Mounted Skylight is the best choice whenever you need a skylight with a low-emission and UV-reflecting double glazing with Argon gas. Contractors all over North America agree that it has a versatile frame design, making it a perfect fit for any retrofit project.

## FEATURES

- Made of material which does not absorb moisture, the window is durable and resistant to corrosion
- Designed for rooms with periodically increased humidity (kitchens, bathrooms)
- Suitable for roof pitches 0-60
- 360° turn-around installation

## SPECIFICATIONS

**FRAME STRUCTURE:** Multi-chamber white PVC profile

**FRAME FINISH:** White PVC profiles from the inside and black from the outside

**GLAZING:** G33 - Low-E tempered over laminated - double-pane glazing unit with warm TGI spacer and Argon gas

**GASKET SYSTEM:** Two rubber gaskets

**WARRANTY:** 10 years for skylight and glazing

For a complete list of options visit  
[www.AccessDoorsAndPanels.com](http://www.AccessDoorsAndPanels.com)

SKU: **FXR L**

## STANDARD FIXED CURB-MOUNTED SKYLIGHT

LAMINATED GLASS



## DIMENSIONS AND APPEARANCE

>> [CLICK TO VIEW ADDITIONAL DETAILS AND PRICING](#) <<

### ADDITIONAL PRODUCTS TO BE USED:



|                               |   |
|-------------------------------|---|
| Flashings                     | EH-C - for roof tiles, corrugated metal and standing seam<br>EL-C - for shingles and shakes |
| Ice and Water Guard           | - Fakro Euroband or similar self-adhesive underlayment                                      |
| Included mounting accessories | - Bit torx t20<br>- Installation screws #10 x 2 in.   |
| External accessories          | - SMZ solar awning blind  |
| Internal accessories          | - SRF blackout blind, SRP light reducing blind  |

For more details see the second page



## PROJECT DATA

**Custom Sizes Available - Fast!**

Scan  or  Click



To view Pricing and  
Additional Product Info.

|                        |  |   |   |         |
|------------------------|--|---|---|---------|
| PROJECT NAME :         | QTY  | W | H | OPTIONS |
| ARCHITECT :            |  |   |   |         |
| DEALER :               |  |   |   |         |
| CONTRACTOR :           |  |   |   |         |
| LOCATION :             | SPECIAL INSTRUCTIONS :                       |   |   |         |
| DATE :                 |  |   |   |         |
| TAGGING INSTRUCTIONS : | SUBMITTAL APPROVAL :<br>(signature or stamp) |   |   |         |



TELEPHONE:  
1-888-457-1275  
FAX:  
1-888-626-2907



PO BOX 66738 #76520,  
SAINT LOUIS, MO  
63166-6738  
USA















WEBSITE:  
[www.AccessDoorsAndPanels.com](http://www.AccessDoorsAndPanels.com)  
E-MAIL:  
[info@AccessDoorsAndPanels.com](mailto:info@AccessDoorsAndPanels.com)



# FXR L

# CURB MOUNTED FIXED SKYLIGHT

**DIMENSIONS:**

| Size                          |                | <br>14/30 | <br>14/46 | <br>22/22 | <br>22/30 | <br>22/34 | <br>22/46 | <br>22/70 | <br>30/30 | <br>30/46 | <br>34/34 | <br>34/46 | <br>46/46 |
|-------------------------------|----------------|--|--|--|--|--|--|--|--|--|--|--|--|
| Outside curb dimensions (WxR) | in.            | 17½ x 33½  | 17½ x 49½  | 25½ x 25½  | 25½ x 33½  | 25½ x 37½  | 25½ x 49½  | 25½ x 73½  | 33½ x 33½  | 33½ x 49½  | 37½ x 37½  | 37½x 49½   | 49½ x 49½  |
| Inside curb dimensions (BxK)  | in.            | 14½ x 30½  | 14½ x 46½  | 22½ x 22½  | 22½ x 30½  | 22½ x 34½  | 22½ x 46½  | 22½ x 70½  | 30½ x 30½  | 30½ x 46½  | 34½ x 34½  | 34½ x 46½  | 46½ x 46½  |
| Outside frame (SxL)           | in.            | 19¼ x 35¼  | 19¼ x 51¼  | 27¼ x 27¼  | 27¼ x 35¼  | 27¼ x 39⅞  | 27¼ x 51¼  | 27¼ x 75   | 35¼ x 35¼  | 35¼ x 51¼  | 39⅞ x 39⅞  | 39⅞ x 51¼  | 51¼ x 51¼  |
| Daylight area (glass)         | sq. ft.<br>in. | 3.12<br>0.29   | 4.63<br>0.43   | 2.45<br>0.23   | 3.49<br>0.32   | 4.01<br>0.37   | 5.58<br>0.52   | 8.71<br>0.81   | 4.98<br>0.46   | 7.95<br>0.74   | 6.57<br>0.61   | 9.13<br>0.85   | 10.70<br>1.18  |

### TECHNICAL PARAMETERS:

| Technical parameters                       | Glazing unit type                       |      |                         |
|--|---|------|-------------------------|
|  | Unit                                    | G33  | Rating                  |
| U-factor                                   | [BTU/h ft²F]                            | 0.45 | NFRC 100                |
| Solar Heat Gain Coefficient                | -                                       | 0.22 | NFRC 200                |
| Air Leakage                                | [cfm/ft²] @ 1,57 psf, tested size 24x70 | 0.06 | NFRC 400                |
| Visible Transmittance                      | -                                       | 0.42 | NFRC 200                |
| UV protection                              | -                                       | 99.7 | EN 410-2011             |
| Condensation Resistance                    | -                                       | 62   | NFRC 500                |
| Water Penetration Resistance Test Pressure | [Pa]                                    | 720  | (NAFS 2011) & A440S1-17 |

\*for windows wider or longer than 55"

