

## FIRE EXTINGUISHERS - Cosmic Multi-Purpose Dry Chemical - Portable Handheld

ABC dry chemical is a multipurpose extinguishing agent that is suitable for use in offices, classrooms, churches, parking garages and retail. Not recommended for use on sensitive electronic equipment.



**CLASS A FIRES**  
Common  
Combustibles



**CLASS B FIRES**  
Flammable Liquids  
and Gases



**CLASS C FIRES**  
Energized Electrical  
Equipment

### SPECIFICATIONS:

These units contain specially fluidized and siliconized mono ammonium phosphate powder, which smothers and breaks the chain reaction on Class B fires, fuses and insulates Class A fires and is a non-conductor of electricity. Non-toxic.

Conforms to Test Standards: CAN/ULC-S504 — ANSI/UL299 & CAN/ULC S508 — ANSI/UL711

Operation: Squeeze the lever, which opens the valve, allowing the chemical to be forced out. Upright squeeze grip operation.

Temperature Range: -65° F (-53° C) to 120° F (49° C)

Construction: Heavy-duty steel cylinder with siphon tube, replaceable molded valve stem seal, visual pressure gauge, pull pin and upright squeeze grip. Corrosion and impact-resistant powder coat finish.

Valve Material: Aluminum

### OPTIONS AT ADDITIONAL COST:

	Options	Available Models
	Brass Valve Steel Cylinder	Cosmic 5E, Cosmic 6, Cosmic 10, Cosmic 20
	Aluminum Valve Chrome Cylinder	Cosmic 2.5, Cosmic 5, Cosmic 6 Cosmic 10
	Brass Valve Chrome Cylinder	Cosmic 5, Cosmic 6, Cosmic 10

*Dimensions of extinguishers with above options may vary from table below*

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can be used where required by local codes such as OSHA.

Qty.	Model	Type	Nominal Capacity	Shipping Weight	Cylinder Dia. In Inches	Overall Height In Inches	Overall Width In Inches	Shipping Vol. Approx.	UL Rating	Optional Mounting Bracket	USCG Approved
	Cosmic 2-1/2E*	ABC Dry Chemical	2-1/2 lbs.	5.5 lbs.	3-3/8	15-1/2	5-3/4	.2 cu.ft.	1A-10B:C	MB817C or MB817A*	YES
	Cosmic 5E		5 lbs.	10 lbs.	4-1/4	16-3/8	7-1/4	.35 cu.ft.	3A-40B:C	MB818C or MB818A	YES
	Cosmic 5B		5 lbs.	10 lbs.	4-1/4	16-3/8	7-1/4	.35 cu.ft.	3A-40B:C	MB818C or MB818A*	YES
	Cosmic 5X		5 lbs.	9.25lbs.	4-1/4	15-1/4	7-1/4	.35 cu.ft.	2A-10B:C	MB818A*	YES
	Cosmic 6E		6 lbs.	12.75 lbs.	5	16	7-3/4	.5 cu.ft.	3A-40B:C	MB808A	YES
	Cosmic 10E		10 lbs.	18.25 lbs.	5-1/8	21	7-3/4	.65 cu.ft.	4A-80B:C	MB846C or MB846A	YES
	Cosmic 20E (FE20C)		20 lbs.	33.5 lbs.	7-1/2	21-1/4	8-3/4	1.0 cu.ft.	10A-120B:C	MB811C	YES
	Cosmic 20E (FE20A)		20 lbs.	38 lbs.	7	24	10-1/4	1.0 cu.ft.	10A-120B:C	MB810A	YES

\*Indicates mounting bracket standard. J hook wall bracket standard with all other extinguisher - mounting bracket available for those models at extra charge.

**Note:** NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.



**Access Doors and Panels**  
www.AccessDoorsAndPanels.com  
info@accessdoorsandpanels.com  
Phone: 1-800-609-2917  
Fax: 1-888-626-2907

Distributor:

Contractor:

Date:

Scale: N/A

Project:

Approved By:

Architect:

Item #:

Pages: 1 of 1