

FIRE EXTINGUISHERS - Sentinel Carbon Dioxide - Portable Handheld

Carbon dioxide is a trusted non-conductive clean agent that is more effective for dealing with electronic equipment fires. Typically used in offices, classrooms, retail and research facilities.



CLASS B FIRES
Flammable Liquids
and Gases



CLASS C FIRES
Energized Electrical
Equipment

SPECIFICATIONS:

This extinguisher contains liquid carbon dioxide under pressure.

Conforms to Test Standards: CAN/ULC-S503, ANSI/UL154 & CAN/ULC-S508-ANSI/UL711

Operation: Squeeze the lever, which opens the valve, allowing the carbon dioxide to be forced out. The discharge, which changes into a gas and appears as a smothering cloud of white snow, is then directed to the fire through a funnel-shaped horn. Electrically non-conductive.

Temperature Range: -22° F (-30° C) to 120° F (49° C)

Construction: Lightweight, high-pressure, aluminum cylinder with O-ring seal and straight thread brass valve. The Sentinel is absolutely rust-free and up to 30% lighter than CO2 units with steel cylinders.

Options	Available Models
Non-Magnetic	Sentinel 5*

*Tested to 11.7 Tesla

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. Tested and listed by UL to meet construction and performance standards for this type of extinguisher, and can be used where required by local codes such as OSHA.

Qty.	Model	Type	Nominal Capacity	Shipping Weight	Cylinder Dia. In Inches	Overall Height In Inches	Overall Width In Inches	Shipping Vol	UL Rating	Optional Mounting Bracket	USCG Approved
	Sentinel 5	Carbon Dioxide	5 lbs.	14 lbs.	5-1/4	17-3/4	8-1/4	.65 cu.ft.	5B:C	MB809C or MB809A	YES
	Sentinel 10		10 lbs.	28.25 lbs.	7	24	12	1.3 cu.ft.	10B:C	MB810C or MB810A	YES
	Sentinel 15		15 lbs.	37.75 lbs.	7	30	12	1.0 cu.ft.	10B:C	MB810C or MB864A	YES
	Sentinel 20		20 lbs.	50.75 lbs.	8	30	13	2.1 cu.ft.	10B:C	MB811C or MB811A	YES

J Hook wall bracket standard - Mounting bracket available at extra charge.

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.



Access Doors and Panels
www.AccessDoorsAndPanels.com
info@accessdoorsandpanels.com
Phone: 1-800-609-2917
Fax: 1-888-626-2907

Distributor:		Project:	
Contractor:		Approved By:	
Date:		Architect:	
Scale: N/A	Pages: 1 of 1	Item #:	