

APPLICATION

Folding attic ladders enable safe and easy access to non-inhabited spaces without the need for installing costly and space consuming staircases. Insulated metal model

– LML for garages, inside houses, projects with insulation requirements.

FEATURES

- Insulated door with white finish
- Telescopic plastic ends
- Weather seal gasket
- Ladder unloading mechanism, built in the handrail
- Non-slip steps
- System of adjusting the ladder length to the ceiling height
- Quick installation in the ceiling
- White metal trim
- Additional accessories available
- 2 years warranty

SPECIFICATIONS

HATCH:

Insulated, sandwich type, white

Thickness: 1 3/8"

Thermal insulation thickness: 1 1/8"

No lock – unloading mechanism automatically presses the hatch to the box, opening with the use of a control rod.

FRAME:

Pinewood ladder box includes a steel frame, finishing linings slats and a quick installation system.

Height: 12 3/8"

Seal: 1 pcs

LADDER:

Metal

Ladder width: 15 1/8"

Distance between steps: 9 3/4"

STEPS:

Metal, equipped with anti-slip profile.

Steps width: 5 1/8"

Length: 13 3/4"

STANDARD ACCESSORIES:

Retractable stile ends.

Red handrail with ladder unfolding mechanism control rod for opening the hatch.

White metal trim.

Installation brackets.

SKU: **LML**

METAL FOLDING ATTIC LADDERS



DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

DIMENSIONS:

Rough Opening	Room Height
23.5" x 47"	7'7 3/4" - 9'2 1/4"
27.5" x 47"	
27.5" x 51"	8'4 3/4" - 10'3" *

TECHNICAL PARAMETERS:


Maximum loading	350 lbs
Heat transfer coefficient	R-value: 5.2

COMPATIBLE ACCESSORIES:

Ladder Balustrade LXB-U	The balustrade is available in one standard size 30"x54" for all attic ladders.
Box extension LXN	The standard box height is 4". While ordering the LXN please provide ladder type and size.
Upper hatch LXW	The height of the upper hatch box is 7 3/4".



ASSEMBLY INFORMATION

The LML Attic Ladder is delivered to the customer fully assembled and does not require any pre-installation work. Installation of the product must be carried out in accordance with the included fitting instructions.



For more details see the second page

PROJECT DATA

Scan  or  Click



To view Pricing and Additional Product Info.

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			



TELEPHONE:
1-888-457-1275
FAX:
1-888-626-2907



PO BOX 66738 #76520,
SAINT LOUIS, MO
63166-6738
USA






WEBSITE:
www.AccessDoorsAndPanels.com
E-MAIL:
info@AccessDoorsAndPanels.com



LML

FOLDING METAL SECTION LOFT LADDER

SIZE:				
LML		23½ x 47	27½ x 47	27½ x 51
Ceiling height	H	7'7¾" - 9' 2¼"		8'4¾" - 10'3"*
Rough opening	AxB	23½" x 47"	27½" x 47"	27½" x 51"
Outside frame dimensions		23" x 46¾"	27" x 46⅝"	27" x 50⅝"
Outside frame dimensions including trim		25½" x 48¼"	28½" x 48¼"	28½" x 52¼"
Internal dimensions		21⅝" x 44⅞"	25½" x 44⅞"	25¼" x 48⅞"
Projection	R	65¾"		70"
Landing space	C	47¼"		51¼"
Folder ladder height	K	12½"		
Frame height		12½"		
Approx. Weight (lb.)		119	121	128

* H max - 10'3"
(stile ends maximum extension)

