

APPLICATION

Folding section attic ladder LMP allows access to the attic space, even in very high rooms, while maintaining maximum comfort and safety of use. Supported room height range from 9'10" to 12'.

FEATURES

- Insulated door with white finish
- Plastic ends
- Weather seal gasket
- Ladder unloading mechanism, built into the handrail
- Non-slip steps
- Up to 1½" ceiling height adjustment
- Intended for installation in high ceiling
- Additional accessories available
- 2 years warranty

SPECIFICATIONS

HATCH:

Insulated, sandwich type
Thickness: 1⅝".
Thermal insulation thickness: 1⅝".

FRAME:

Pinewood
Height: 7⅞"
Seal: 1x

LADDER:

Metal
Ladder width: 15"
Stringer height: 3⅞"
Distance between steps: 9½".

STEPS:

Metal, equipped with anti-slip profile.
Step width: 3⅞"
Length: 13⅜"

STANDARD ACCESSORIES:

Plastic ends
Handrail with unloading mechanism.
Lightweight aluminum telescopic rod to open the hatch.

SKU: **LMP**

METAL FOLDING ATTIC LADDERS



DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

DIMENSIONS:

Rough Opening	Room Height
22.5" x 56.5"	7' 11" – 10' 1"
25" x 56.5"	
25" x 56.5"	
30" x 56.5"	

Step length	E	13⅞"
Distance between steps		3⅞"
Distance between steps		9½"

TECHNICAL PARAMETERS:

Maximum loading	375 lbs
Heat transfer coefficient	R-value: 5.2

COMPATIBLE ACCESSORIES:

Ladder Balustrade LXB-U	The balustrade is available in one standard size 30"x54" for all attic ladders.
Wooden trim LXL-W	The trims are available in size 30"x56,5" for smaller sizes have to be cut.
PCV trim LXL-PVC	The trims are available in size 30"x56,5" for smaller sizes have to be cut.
Box extension LXN	The standard box height is 4". While ordering the LXN please provide ladder type and size.
Upper hatch LXW	The height of the upper hatch box is 7¾".
Installation brackets L XK	Maximum ceiling 13¾"

For more details see the second page



ASSEMBLY INFORMATION

The LMP attic ladder is delivered to the customer fully assembled, it requires only screwing side elements of the supports which for transport purposes are unscrewed. The length of the last segment should be cut on-site to suit to existing ceiling height. Installation of the product must be carried out in accordance with the included fitting instructions.

PROJECT DATA

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			

Scan  or  Click



To view Pricing and Additional Product Info.



TELEPHONE:
1-888-457-1275
FAX:
1-888-626-2907



PO BOX 66738 #76520,
SAINT LOUIS, MO
63166-6738
USA






WEBSITE:
www.AccessDoorsAndPanels.com
E-MAIL:
info@AccessDoorsAndPanels.com



LMP

FOLDING SECTION ATTIC LADDER

SIZE:				
LMP		22½ x 56½	25 x 56½	30 x 56½
Manufacturer's part number		869331	869332	869333
Ceiling height	H	9'10" - 12"		
Rough opening	AxB	22½" x 56½"	25" x 56½"	30" x 56½"
Outside frame dimensions		22" x 56"	24½" x 56"	29½" x 56"
Internal frame dimensions		20½" x 54¾"	22⅞" x 54¾"	28" x 54¾"
Projection	R	77⅞"		
Landing space	C	57⅞"		
Folder ladder height	K	12⅝"		
Frame height		7⅞"		
Approx. Weight (lbs)		102	108	114

