Insulated Access Door

DOOR : 20 gauge cold rolled steel
FRAME : 16 gauge cold rolled steel
HINGE : IT: Flush continuous piano
IW/IP: Concealed pin
FINISH : Gray powder paint
INSULATION : 2 thick fire rated mineral fiber
CERTIFICATION : UL listed B label for 1-1/2 hrs (vertical)
Warnock-Hersey listed for 3 hrs (horizontal)

FIRE-RATED

CUSTOM SIZING

BITK1212

BI [FLANGE] [LATCH] [WIDTH] X [HEIGHT] [OPTIONS]

FLANGE	
T	1 Flange
W	Drywall bead
P	Plaster casing

LATCH	
K	Knurled knob / key operated latch bolt
M	Mortise lock (1-1/8) prep

STANDARD SIZES (WIDTH & HEIGHT)				
8 x 8	14 x 14	22 x 22	24 x 36	36 x 48 *
10 x 10	16 x 16	22 x 30	24 x 48 *	48 x 48 *
12 x 12	18 x 18	22 x 36	30 x 30 *	
12 x 18	18 x 24	24 x 24	32 x 32 *	
12 x 24	20 x 30	24 x 30	36 x 36 *	

OPTIONS	
B	Bonderized / galvanized
G	Gasketing
M	Masonry anchors
S	T304 Stainless steel

Custom sizes are available. Rough opening is door size + 1/4.
** Vertical applications only.*

Uninsulated Access Door

DOOR : 14 gauge cold rolled steel
FRAME : 16 gauge cold rolled steel
HINGE : UT: Flush continuous piano
UW/UP: Concealed pin
FINISH : Gray powder paint
CERTIFICATION : UL listed B label for 1-1/2 hrs

FIRE-RATED

VERTICAL ONLY

CUSTOM SIZING

BUTK1212

BU [FLANGE] [LATCH] [WIDTH] X [HEIGHT] [OPTIONS]

FLANGE	
T	1 Flange
W	Drywall bead
P	Plaster casing

LATCH	
K	Knurled knob / key operated latch bolt
M	Mortise lock (1-1/8) prep

STANDARD SIZES (WIDTH & HEIGHT)			
8 x 8	16 x 16	22 x 36	32 x 32
10 x 10	18 x 18	24 x 24	36 x 36
12 x 12	18 x 24	24 x 30	36 x 48
12 x 18	20 x 30	24 x 36	
12 x 24	22 x 22	24 x 48	
14 x 14	22 x 30	30 x 30	

OPTIONS	
B	Bonderized / galvanized
G	Gasketing
M	Masonry anchors
S	T304 Stainless steel

Custom sizes are available. Rough opening is door size + 1/4.

FF Systems
Access Panels