

Doors are designed for use with acoustical tile or gypsum board walls and ceilings. The door is engineered to install flush, virtually concealed. Door is recessed 5/8" to accept acoustical tile or gypsum board.

Door is 16 gauge and **frame** is 16 gauge, galvannealed steel with a white prime coat finish.

Concealed Hinge operates completely out of sight so that only the metal thickness of the door and frame is visible.

Latch is screwdriver operated.

SUBMITTAL/TECHNICAL DATA SHEET





■ DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

GUIDE SPECIFICATION

Access door shall be fabricated from 16 gauge and frame from 16 gauge, galvannealed steel with a white prime coat finish. Door shall be recessed 5/8" to accept acoustical tile or gypsum board.

Hinge shall be concealed type. Latch shall be screwdriver operated.

MODEL NUMBER AND OPTIONS SELECTION

BASE MODEL NUMBER

☐ -AT Acoustical Tile Access Door


SUFFIX OPTIONS

□ -AKL Allen Key Latch
□ -GB Galvanized Drywall Bead
□ -CL Cylinder Lock (one per door)
□ -CLD Cylinder Lock with Dust Shutter (one per door)


Shutter (one per door)
□ -SS Stainless Steel Construction
(Type 304 No. 4 Satin Finish)

STANDARD SIZES:

DOOR SIZE (W X H)	CEILING OPENING (Minimum Required)	LATCHES	WEIGHT
AT 8" x 8"	8-1/8" x 8-1/8"	1	4 lbs.
AT 12" x 12"	12-1/8" x 12-1/8"	1	5.5 lbs.
AT 12" x 24"	12-1/8" x 24-1/8"	2	9.5 lbs.
AT 16" x 16"	16-1/8" x 16-1/8"	2	8.5 lbs.
AT 18" x 18"	18-1/8" x 18-1/8"	2	10 lbs.
AT 24" x 24"	24-1/8" x 24-1/8"	4	16 lbs.
AT 24" x 36"	24-1/8" x 36-1/8"	5	24.5 lbs.



FRONT VIEW



NOTES:

- 1. TILE, BY OTHERS
- 2. CONCEALED HINGE
- 3. MOUNTING HOLES
- 4. SCREWDRIVER OPERATED LATCH
- 5. FRAME

For a complete list of options visit www.AccessDoorsAndPanels.com

■ PROJECT DATA

Custom Sizes Available - Fast!





To view Pricing and Additional Product Info.





PO BOX 66738 #76520, SAINT LOUIS, MO 63166-6738 USA



WEBSITE:

www.AccessDoorsAndPanels.com