

SUBMITTAL/TECHNICAL DATA SHEET



DESCRIPTION

The Surface Mount Floor Door is designed for retrofit applications with internal flanges for easy mounting. This door is an economical option for areas where water or moisture intrusion is not a concern.

FEATURES

- Light Pedestrian Load
- Security Closure
- Interior Angle Frame (Flange)

SPECIFICATIONS

LOAD: 150psf

DOOR: Single Leaf

MATERIAL: Aluminum 3/16 inch, mill finish.

COVER: Diamond tread plate.

FRAME: Interior angle (flange).

INSTALLATION: Surface mount, mechanically fastened.

SPRING: Coil Type 17-7 Stainless Steel, enclosed in Type 316 Stainless Steel telescopic tubes.

HINGE: Heavy-duty Type 316 Stainless Steel.

HOLD OPEN ARM: Type 316 Stainless Steel automatic hold open arm with red vinyl grip handle, locks cover in open position.

MINIMUM SIZE: 24 in. X 24 in.

MAXIMUM SIZE: 48 in. X 48 in

LATCH: Slam latch Type 316 Stainless Steel with inside lever handle, includes removable 5/16 inch steel square "L" handle and threaded plug.

OPTIONS: Padlock Hasps, Locks, Finishes, Gasket, Safety Grates, Safety Nets, Safety Rails, Skirting.

WARRANTY: 5 year

For a complete list of options visit www.AccessDoorsAndPanels.com



DIMENSIONS AND APPEARANCE


>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

ORDER GUIDE:

MODEL	WIDTH	X	LENGTH	SELN
BFDNLA				
	24" X 24"			
	30" X 30"			
	30" X 36"			
	36" X 36"			
	42" X 42"			

Additional sizes and options available, call for more information.

FRAME:





Angle Frame
Cast-in

PROJECT DATA

Custom Sizes Available - Fast!

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :	SUBMITTAL APPROVAL :			
TAGGING INSTRUCTIONS :	(signature or stamp)			

Scan  or  Click



To view Pricing and Additional Product Info.

TELEPHONE:
1-888-457-1275
FAX:
1-888-626-2907



PO BOX 66738 #76520,
SAINT LOUIS, MO
63166-6738
USA



WEBSITE:
www.AccessDoorsAndPanels.com
E-MAIL:
info@AccessDoorsAndPanels.com