



# SUBMITTAL/TECHNICAL DATA SHEET

## APPLICATION

ABC dry chemical is a multipurpose extinguishing agent that is suitable for use in offices, classrooms, churches, parking garages and retail. Not recommended for use on sensitive electronic equipment.

## DESCRIPTIONS

These units contain specially fluidized and siliconized mono ammonium phosphate powder, which smothers and breaks the chain reaction on Class B fires, fuses and insulates Class A fires and is a non-conductor of electricity. Non-toxic.

## SPECIFICATIONS

**CONFORMS TO TEST STANDARDS:**  
CAN/ULC-S504 — ANSI/UL299 &  
CAN/ULC S508 — ANSI/UL711

**OPERATION:** Squeeze the lever, which opens the valve, allowing the chemical to be forced out. Upright squeeze grip operation.

**TEMPERATURE RANGE:** -65° F (-53° C) to 120° F (49° C)

**CONSTRUCTION:** Heavy-duty steel cylinder with siphon tube, replaceable molded valve stem seal, visual pressure gauge, pull pin and upright squeeze grip. Corrosion and impact resistant powder coat finish.

**VALVE MATERIAL:** Aluminum

**CAPACITY:** 2-1/2, 5, 6, 10, 20 lbs

**CLASS:** A,B,C Fires

SKU: **COSMIC**

## COSMIC EXTINGUISHERS

MULTI PURPOSE DRY CHEMICAL



## DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

### STANDARD DIMENSIONS:

Model	Type	Valve	Nominal Capacity	Ship. Weight	Cylinder Dia.	Overall Height	Overall Width	Ship. Vol.	UL Rating @ 68°F	Optional Mount. Bracket
Cosmic 2-1/2E* (FE02C)	ABC Dry Chemical	Aluminum	2-½ lbs.	5-½ lbs.	3-¾"	15-½"	5-¾"	.2 cu.ft.	1A-10B:C	MB817C*
Cosmic 5E (FE05C)			5 lbs.	10 lbs.	4-¼"	16-¾"	7-¾"	.35 cu.ft.	3A-40B:C	MB818C
Cosmic 5B* (FE05BC)			5 lbs.	10 lbs.	4-¼"	16-¾"	7-¾"	.35 cu.ft.	3A-40B:C	MB818C*
Cosmic 10E (FE10C)			10 lbs.	18-¼ lbs.	5-½"	21"	7-¾"	.65 cu.ft.	4A-80B:C	MB846C
Cosmic 20E (FE20C)			20 lbs.	33-½ lbs.	7-½"	21-¼"	8-¾"	1.0 cu.ft.	10A-120B:C	MB811C
Cosmic 5E (FE05CBV)		Brass	5 lbs.	10 lbs.	4-¼"	16-¾"	7-¼"	.35 cu.ft.	3A-40B:C	MB818C
Cosmic 10E (FE10CBV)			10 lbs.	18-¼ lbs.	5-½"	21"	7-¾"	.65 cu.ft.	4A-80B:C	MB846C
Cosmic 20E (FE20CBV)			20 lbs.	33-½ lbs.	7-½"	21-¼"	8-¾"	1.0 cu.ft.	10A-120B:C	MB811C

\*Indicates mounting bracket standard. J hook wall bracket standard with all other extinguisher

- mounting bracket available for those models at extra charge.

- These all products are USCG approved.

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.



### CLASS A FIRES

Common  
Combustibles



### CLASS B FIRES

Flammable  
Liquids and Gases





### CLASS C FIRES

Energized  
Electrical Equipment

## PROJECT DATA

Custom Sizes Available - Fast!

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :	SUBMITTAL APPROVAL : (signature or stamp)			
TAGGING INSTRUCTIONS :				

Scan  or  Click



To view Pricing and  
Additional Product Info.



TELEPHONE:  
1-888-457-1275  
FAX:  
1-888-626-2907



PO BOX 66738 #76520,  
SAINT LOUIS, MO  
63166-6738  
USA



WEBSITE:  
www.AccessDoorsAndPanels.com  
E-MAIL:  
info@AccessDoorsAndPanels.com