

Doors are ideally suited for new installations or for remodeling in masonry, tile, wood or other wall and ceiling surfaces. Door features rounded safety corners.

Door and Frame are fabricated from 16 gauge, galvannealed steel with a white prime coat finish.

Frame is one piece construction, 1" wide and provides perfect concealment of the rough wall opening. Wall frame is provided with 1/4" mounting holes for fastening within the furred spaces allowing faster installation and fixing maximum clearance.

Concealed Pivoting Rod Hinge prevents distortion and closes door squarely. Doors 24" or larger are provided with a continuous piano hinge

Latch is screwdriver operated.

Finish is a white prime coat suitable for painting

GUIDE SPECIFICATION

Dry Wall Access Doors (Specify model number and options.) Access door and frame shall be fabricated from 16 gauge, galvannealed steel with a white prime coat finish. The door shall have rounded safety corners and a concealed pivoting rod hinge Frame shall be one piece construction with no miters or welds on the face. Latch shall be screwdriver operated. Finish shall be a white prime coat suitable for painting.

MODEL NUMBER AND **OPTIONS SELECTION**

DACE	MODEL	
BASE		. NUMBER

🗆 -DW	Dry Wall Access Door (16 Gauge Steel)
SUFFIX	OPTIONS
🗆 -AKL	Allen Key Latch
🗆 -CL	Cylinder Lock (one per door)
🗆 -CLD	Cylinder Lock with Dust Shutter (one per door)
🗆 -MAS	Masonry Anchor Straps
🗆 -MLP	Mortise Cylinder Lock (Prep)
🗆 -SS	Stainless Steel Construction

'T' Handle □ -TH

For a complete list of options visit www.AccessDoorsAndPanels.com



To view Pricing and Additional Product Info.

SUBMITTAL/TECHNICAL DATA SHEET

DRY WALL ACCESS DOOR




DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

STANDARD SIZES:

SKU: DN

DOOR SIZE (W x H)	WALL OPENING	LOCK QTY	WEIGHT LBS
DW 6" x 6"	6-1/2" x 6-1/2"	1	3.0 LBS.
DW 8" x 8"	8-1/2" x 8-1/2"	1	3.0 LBS.
DW 8" x 12"	8-1/2" x 12-1/2"	1	4.0 LBS.
DW 10" x 10"	10-1/2" x 10-1/2"	1	4.0 LBS.
DW 12" x 12"	12-1/2" x 12-1/2"	1	5.5 LBS.
DW 12" x 16"	12-1/2" x 16-1/2"	1	6.0 LBS.
DW 12" x 18"	12-1/2" x 18-1/2"	2	6.5 LBS.
DW 12" x 24"	12-1/2" x 24-1/2"	3	9.5 LBS.
DW 14" x 14"	14-1/2" x 14-1/2"	1	6.0 LBS.
DW 14" x 20"	14-1/2" x 20-1/2"	3	8.0 LBS.
DW 14" x 24"	14-1/2" x 24-1/2"	3	15.0 LBS.
DW 15" x 15"	15-1/2" x 15-1/2"	1	6.5 LBS.
DW 16" x 16"	16-1/2" x 16-1/2"	1	7.5 LBS.
DW 16" x 20"	16-1/2" x 20-1/2"	3	8.5 LBS.
DW 16" x 24"	16-1/2" x 24-1/2"	3	10.0 LBS.
DW 18" x 18"	18-1/2" x 18-1/2"	3	9.0 LBS.
DW 18" x 24"	18-1/2" x 24-1/2"	5	12.0 LBS.
DW 18" x 36"	18-1/2" x 36-1/2"	6	16.0 LBS.
DW 20" x 20"	20-1/2" x 20-1/2"	3	11.0 LBS.
DW 20" x 24"	20-1/2" x 24-1/2"	5	13.0 LBS.
DW 20" x 30"	20-1/2" x 30-1/2"	5	15.0 LBS.
DW 22" x 22"	22-1/2" x 22-1/2"	3	12.0 LBS.
DW 22" x 30"	22-1/2" x 30-1/2"	5	16.0 LBS.
DW 22" x 36"	22-1/2" x 36-1/2"	6	22.0 LBS.
DW 24" x 24"	24-1/2" x 24-1/2"	3	15.0 LBS.
DW 24" x 30"	24-1/2" x 30-1/2"	5	17.0 LBS.
DW 24" x 36"	24-1/2" x 36-1/2"	6	20.5 LBS.
DW 24" x 48"	24-1/2" x 48-1/2"	7	28.0 LBS.
DW 30" x 30"	30-1/2" x 30-1/2"	7	21.5 LBS.
DW 30" x 36"	30-1/2" x 36-1/2"	8	29.0 LBS.
DW 32" x 32"	32-1/2" x 32-1/2"	7	23.0 LBS.
DW 36" x 36"	36-1/2" x 36-1/2"	8	31.5 LBS.
DW 36" x 48"	36-1/2" x 48-1/2"	9	42.0 LBS.
DW 48" x 48"	48-1/2" x 48-1/2"	11	58.0 LBS.



SIDE VIEW

NOTES:

1. CONCEALED PIVOTING ROD HINGE 2. DOOR

3. FRAME

4. SCREWDRIVER OPERATED LATCH

5. MOUNTING HOLES

Custom Sizes Available - Fast!

PROJECT NAME :	QTY	W	н	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL	SPECIAL INSTRUCTIONS :		
DATE :				
TAGGING INSTRUCTIONS :		SUBMITTAL APPROVAL : (signature or stamp)		



PROJECT DATA



PO BOX 66738 #76520, SAINT LOUIS, MO 63166-6738



WEBSITE: www.AccessDoorsAndPanels.com

E-MAIL: info@AccessDoorsAndPanels.com