


DETAIL & SUBMITTAL SHEET



FRONT ELEVATION

This fire-rated door can be used wherever it is necessary to provide service access to shafts and any other location which must have a fire rating. Approved for wall and ceiling use.

Anchor straps standard on all fire-rated doors



SPECIFICATIONS:

Door: 18 ga. steel

Frame: 16 ga. steel, 2 1/2" deep

Insulation: 2" thick mineral wool (THERMAFIBER®), in between two pieces of 22 ga. steel

Hinge: Fully concealed, pivot rod type hinge. Allows opening to 140°

Latches: Knurled knob lock & 1 Flush key

Automatic Panel Closer: Furnished on all doors. vertical position only. Ceiling position requires self-assisted closing

Inside Panel Release: Furnished on all doors

Finish: Grey baked enamel coat

Ceiling Installation: To comply with current fire regulations, largest size acceptable is 24" x 36"

OPTIONS (at additional cost)

Finishes:

Stainless Steel Type 304 No. 4 Satin Finish

Brushed

Stainless Steel Type 316 No. 4 Satin Finish Brushed

Options: (additional cost)

Mortise Best Lock


Hot Smoke Seal gasketing all 4 sides**

Special sizes available


[Click here to Online Product Page and Pricing](#)

SECTION DETAIL

Fire-rated access door for ceiling and wall installation



NOTE: For fire-rated ceiling access doors, on size 16" x 16" and larger, extra spring supplied with door must be attached from back of door pan to framing or floor above. In horizontal (ceiling) applications door has self-assisted closing.



UL US 1-1/2 hour "B" label 450 degrees F (250 degrees C) maximum temperature rise in 30 minutes for vertical wall installations only. Test file number R-10364. This door may be used in a two hour fire rated wall assembly

Warnock Hersey International; 1 hour fire rated combustible floor and ceiling assembly - Report # WHI-495-PSH-0191

Warnock Hersey International; 3 hour fire rated non-combustible floor and ceiling assembly - Report # WHI-495-PSH-0192

** Hot Smoke Seal™ fire tested: Listed to meet the requirements of standards UL10B, UL10C, UBC 7-2, Part 1 and BS476: 1987 for application to fire rated door assemblies.



THERMAFIBER® Industrial Felt insulation for optimal fire protection (rated noncombustible by NFPA Standard 220 when tested in accordance with ASTM E136 and withstands ASTM E119) and superior sound control USG tested per ASTM C165: 8 pcf STC 15-2" thickness

Item No.	Door Size W x H	Wall Opening	Slam Catch	Ship Wt. Lbs.
FR 800	8 x 8	8 1/4 x 8 1/4	1	8
FR 800	10 x 10	10 1/4 x 10 1/4	1	10
FR 800	12 x 12	12 1/4 x 12 1/4	1	12
FR 800	12 x 18	12 1/4 x 18 1/4	1	12
FR 800	12 x 24	12 1/4 x 24 1/4	1	19
FR 800	14 x 14	14 1/4 x 14 1/4	1	14
FR 800	16 x 16	16 1/4 x 16 1/4	1	17
FR 800	18 x 18	18 1/4 x 18 1/4	1	21
FR 800	18 x 24	18 1/4 x 24 1/4	1	26
FR 800	20 x 20	20 1/4 x 20 1/4	1	24
FR 800	20 x 24	20 1/4 x 24 1/4	1	26
FR 800	20 x 30	20 1/4 x 30 1/4	1	32
FR 800	21 x 36	21 1/4 x 36 1/4	1	37
FR 800	22 x 22	22 1/4 x 22 1/4	1	28
FR 800	22 x 24	22 1/4 x 24 1/4	1	29
FR 800	22 x 30	22 1/4 x 30 1/4	2	39
FR 800	22 x 36	22 1/4 x 36 1/4	2	47
FR 800	24 x 24	24 1/4 x 24 1/4	1	32
FR 800	24 x 30	24 1/4 x 30 1/4	2	43
FR 800	24 x 36	24 1/4 x 36 1/4	2	48
FR 800	24 x 48	24 1/4 x 48 1/4	2	62
FR 800	30 x 30	30 1/4 x 30 1/4	2	50
FR 800	32 x 32	32 1/4 x 32 1/4	1	60
FR 800	36 x 36	36 1/4 x 36 1/4	2	67
FR 800	36 x 48	36 1/4 x 48 1/4	2	88
FR 800	48 x 48	48 1/4 x 48 1/4	2	104

AccessDoorsAndPanels

Phone: 1-800-609-2917
 Fax: 1-888-626-2907

Email: info@accessdoorsandpanels.com
 Website: www.AccessDoorsAndPanels.com
 PO Box 66738 #76520, Saint Louis, MO 63166 6738



www.AccessDoorsAndPanels.com