



Quality Access Doors - FAST !



FIRE RATED INSULATED - UPSWING DOOR FOR CEILINGS

BA-FW-5050-UP

Application

- An insulated, fire rated access door for inward opening in ceilings

Product Features

- For fire rated ceilings, this door has been approved by Warnock Hersey International for 3 hours (max. size to 24" x 36")
- Insulated Door Panel
- Self-Closing
- Self-Latching
- Inside Latch Release

BA-FW-5050-UP Access Door Specifications:

Material: Steel or Stainless Steel

Door: 16 gauge, Flush to frame with reinforced edges filled with 2" thick fire insulation

Mounting Frame: 16 gauge mounting frame, with trim 1" wide

Hinge: Concealed with coil spring for dampening

Fire Rating (Walls): UL — 1-1/2 hour "B" label. ULC — 2 hour "B" label.

Max size: 24 x 36. For Ceilings: Warnock Hersey International 3 hour rated in a non-combustible ceiling. 1 hour rated in a combustibile ceiling. Max size: 24x 36

Standard Latch: L Handle - operable from both sides

Finish: Steel: 5 stage iron phosphate preparation with prime coat of white baked-on enamel.

Stainless Steel: Type 304 - #4 satin polish



STANDARD SIZES (Special sizes available upon request)

| NOMINAL DOOR SIZE W X H | | WEIGHT PER DOOR | | |
|-------------------------|-----------|-----------------|------|------|
| inches | mm | Latches | lbs. | kg. |
| 22 X 36 | 560 X 914 | 2 | 35 | 15.9 |
| 24 X 24 | 610 X 610 | 1 | 28 | 12.7 |
| 24 X 36 | 610 X 914 | 2 | 38 | 18.1 |

Wall or ceiling opening is W + 1/2" (12 mm)
For detailed specifications see submittal sheet

