



# SUBMITTAL/TECHNICAL DATA SHEET

## APPLICATION

Standard BC dry chemical is a multipurpose that is suitable for use on flammable liquid hazards in areas such as light manufacturing facilities, vehicle/aircraft/marine service centers and retail stores.

## DESCRIPTIONS

These models contain a siliconized sodium bicarbonate base, the traditional dry chemical. Cleanup after use is generally easy, because the chemical does not normally bake to a hot metal surface. Non-toxic.

## SPECIFICATIONS

CONFORMS TO TEST STANDARDS:  
CAN/ULC-S504-ANSI/UL299 &  
CAN/ULC-S508-ANSI/UL711

**OPERATION:** Squeeze the lever, which opens the valve, allowing the chemical to be forced out. Upright squeeze grip operation.

**TEMPERATURE RANGE:** -65° F (-53° C) to 120° F (49° C)

**CONSTRUCTION:** Heavy-duty steel cylinder with rugged metal valve and siphon tube with replaceable valve stem seal, visual pressure gauge pull pin and upright squeeze grip.

**VALVE MATERIAL:** Aluminum

**NOMINAL CAPACITY:** 2.5 lb

**UL Rating:** 10BC

**CLASS:** B,C Fires

SKU: **GALAXY**

## GALAXY EXTINGUISHERS


### REGULAR DRY CHEMICAL



## DIMENSIONS AND APPEARANCE

>> [CLICK TO VIEW ADDITIONAL DETAILS AND PRICING](#) <<

### STANDARD DIMENSIONS:

Model	Type	Nominal Capacity	Ship. Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol	UL Rating 	Optional Mount. Bracket
Galaxy 2-1/2* (FG02C)	BC Dry Chemical	2-½ lbs.	5.5 lbs.	3-¾"	14-¾"	4-7/8"	.2 cu.ft.	10B:C	MB817C*
Galaxy 5-1/2 (FG055C)		5-½ lbs.	10.5 lbs.	4-¼"	16-¾"	7-¼"	.4 cu.ft.	40B:C	MB818C
Galaxy 10 (FG10C)		10 lbs.	18.25 lbs.	5-½"	21"	8-¾"	.65 cu.ft.	40B:C	MB846C
Galaxy 20 (FG20C)		20 lbs.	33.5 lbs.	7-½"	23-¼"	10-¼"	1.0 cu.ft.	120B:C	MB811C

\*Indicates mounting bracket standard. J hook wall bracket standard with all other extinguisher  
- mounting bracket available for those models at extra charge.  
- These all products are USCG approved.

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.



**CLASS B FIRES**  
Flammable  
Liquids and Gases





**CLASS C FIRES**  
Energized  
Electrical Equipment

For a complete list of options visit  
[www.AccessDoorsAndPanels.com](http://www.AccessDoorsAndPanels.com)

## PROJECT DATA

**Custom Sizes Available - Fast!**

Scan  or  Click



To view Pricing and  
Additional Product Info.

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :				
TAGGING INSTRUCTIONS :	SUBMITTAL APPROVAL : (signature or stamp)			

TELEPHONE:  
1-888-457-1275  
FAX:  
1-888-626-2907



PO BOX 66738 #76520,  
SAINT LOUIS, MO  
63166-6738  
USA



WEBSITE:  
[www.AccessDoorsAndPanels.com](http://www.AccessDoorsAndPanels.com)  
E-MAIL:  
[info@AccessDoorsAndPanels.com](mailto:info@AccessDoorsAndPanels.com)