

SUBMITTAL/TECHNICAL DATA SHEET

INVISAGRILLE

DESCRIPTION

A premium flush mount supply vent cover for a 6"x10" duct. Complete with diffuser flaps to control your air flow, this cover fits into the drywall opening of 7"x11" and has a vented/slotted area of 5"x9".

APPLICATION

- Designed for 1/2" and 5/8" thick drywall.
- Suitable for both wall and ceiling installation.
- Screws on to the face of your drywall.
- Once finished seaming over the flange, the product is ready to be primed and painted to your wall colour.
- The inserts comes primed white and ready for your paint colour.

FEATURES

- Magnetic removable triple fibre reinforced cement board grill.
- 24 gauge galvanized satin coat steel frame complete with a beaded edge and adjustable diffuser.
- 4 rare earth magnets (0.250" diameter x 0.060" thick).
- Easy installation, primed and ready to paint.
- Rectangular straight vent slots.
- Fire Rated, non-flammable.
- Impact Resistant.
- Moisture and Water Resistant, Mold Resistant.
- Eco-Friendly Manufacturing and Non-Hazardous.


SPECIFICATIONS

- Over 16 square inches (103.2 square centimeters) of open area.
- Slot Size: 0.25" x 4.96" (6.35mm x 125.98mm).
- 13 rectangular straight vertical slots.
- Overall dimensions are 13.5" x 9.5" x 0.5" (343mm x 241.3mm x 12mm).
- Product weight is 1.9 pounds (0.86 kilograms)

For a complete list of options visit www.AccessDoorsAndPanels.com

SKU: **IG-MAG-S6X10**


REMOVABLE WALL AND CEILING SUPPLY VENT



DIMENSIONS AND APPEARANCE


>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

CUT YOUR DRYWALL OPENING TO 11.25" X 7.25" TO FIT THE FRAME INSIDE. CENTER OVER 6x10 BOOT.



MATERIAL INFORMATION:

Raw Material: cement, fibres, quartz sand, non-hazardous fillers.
 Density: 1.0 < D ≤ 1.2 g/cm³
 Asbestos Content: 100% asbestos-free
 Fire resistance: non-combustible
 Water Absorption: ≤40%
 Resistant Bending Strength: ≤10.5 MPa dry
 Moisture Movement: 0.25 %
 Freeze Thaw: No distortion after 25 repeated cycles of freezing and thawing .



PROJECT DATA

Custom Sizes Available - Fast!

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :	SUBMITTAL APPROVAL :			
TAGGING INSTRUCTIONS :	(signature or stamp)			

Scan  or  Click



To view Pricing and Additional Product Info.

TELEPHONE:
1-888-457-1275
FAX:
1-888-626-2907

PO BOX 66738 #76520,
SAINT LOUIS, MO
63166-6738
USA




WEBSITE:
www.AccessDoorsAndPanels.com
E-MAIL:
info@AccessDoorsAndPanels.com



IG-MAG-S6X10 6" X 10" REMOVABLE WALL AND CEILING SUPPLY VENT

AIRFLOW DATA

			Core Velocity (FPM)																			
			300	400	500	600	700	800	1000	1200	1400											
Opening Width (in.)	Opening Height (in.)	Core Area (ft ²)	Core Velocity Pressure ("wc)																			
9	5	0.3125	Flow (CFM)											63	85	106	127	148	169	212	254	296
			Static Pressure ("wc)											0.016	0.029	0.045	0.065	0.088	0.115	0.180	0.259	0.352
			Throw (ft) (150 100 50)											3 4 8	3 5 10	4 6 13	5 8 15	6 9 18	7 10 20	13 25	10 15 30	12 18 35



CUT YOUR DRYWALL OPENING TO 11.25" X 7.25" TO FIT THE FRAME INSIDE. CENTER OVER 6x10 BOOT.

