

SUBMITTAL: MODEL CT™ FLUSH ACCESS PANELS



An Access Panel with Recessed Door and Trimless Frame with 14 Gauge Frame.

Designed to accommodate an insert up to 1/2" thickness in the door. Acoustical tile or drywall can be attached to the door with adhesive to be flush with the surrounding tile field. A continuous hinge, located at the outside edge of the door ensures easy opening of the plaster or tile covered panel. Not to be used for suspended ceilings.



Panel shown as partially-covered by acoustic tile



Recessed Door Accepts 1/2" Insert

SPECIFICATIONS:

Door Panel: 16 gauge steel, recess to accommodate 1/2" thick insert.

Frame: 14 gauge steel

Finish: White powder coat paint.

Hinge: Recessed, continuous hinge mounted on the long side of oblong panels.

Lock: Flush screwdriver-operated steel cam standard "C"

Sizes: Minimum 6" x 6" (152.4 x 152.4 mm), maximum 36"x 36"

STEP 1: SELECT MODEL NUMBER AND QUANTITY ON CHART

STEP 2: SELECT MATERIAL

- _____ CT Steel
- _____ CTG Galvanized (Additional Cost)

Please Note - Color Codes and Lock Option Codes have Changed.

Order Format Example: **CT-2424M2W-**

TM - Width Height Lock (C Std or Optional Lock/Latch Code) Color Options

STEP 3: SELECT OPTIONAL FEATURES AT ADDITIONAL COST:

- Optional color Code: _____ - see page 2
- (L) Cylinder lock installed
- (C2) Torx head cam
- (C4) Hex head cam
- (C3) Spanner head cam
- (M1) Mortise cam lock prep 1-1/8" dia, 1-1/4" length
- (M2) Mortise cam lock (06431) installed
- Optional Door Panel Depth (Contact Manufacturer)
- 14 Gauge frame and 14 gauge door



Standard Cam Latch

LATCH AND LOCK OPTIONS

Cylinder Lock (L)	Optional Torx Head Cam (C2)	Optional Spanner Head Cam (C3)	Optional Hex Head Cam (C4)	Mortise Lock (M2)

	Distributor:	Quantity:
	Contractor:	Approved By:
	Model #:	Architect:
	Project:	Date:

SUBMITTAL: MODEL CT™ FLUSH ACCESS PANELS



QTY	A - MODEL SIZE = DOOR SIZE	B - OUTSIDE FRAME DIMENSIONS		SHIPPING WEIGHT APPROX.	LATCH (ES)
	WIDTH X HEIGHT	WIDTH	HEIGHT		
	12" x 12"	12 1/4 "	12 1/4 "	9 lbs	1
	12" x 24"	12 1/4 "	24 1/4 "	14 lbs	2
	18" x 18"	18 1/4 "	18 1/4 "	15 lbs	3
	22" x 30"	22 1/4 "	30 1/4 "	26 lbs	4
	24" x 24"	24 1/4 "	24 1/4 "	24 lbs	4
	24" x 36"	24 1/4 "	36 1/4 "	34 lbs	5
	36" x 36"	36 1/4"	36 1/4"	51 lbs	6

Optional Colors at Additional Cost - Samples Available

G-Gray	R-Red	BK-Black/FB Flat	SI - Silver
S-Sand	AB-AMS Beige	SB-SC Flat Beige	B-Bronze

