



**LEAD LINED ACCESS DOOR
KATR-LL
For Drywall Ceilings**

DATE



AccessDoorsAndPanels
Phone: 1-800-609-2917
Fax: 1-888-828-6021
E-mail: info@accessdoorsandpanels.com
www.AccessDoorsAndPanels.com

PROJECT DATA					
Project Name:					
Architect:					
Contractor:					
Agent/Customer Name:					
Tagging Instructions:					
Special Instructions:					

CONSTRUCTION:

1. Frame shall be 16 gage steel and doors all be 18 gage steel.
2. Door shall be recessed 1 1/2" to accommodate double thickness of wall board.
3. Hinge shall be exposed, continuous piano hinge.
4. Locks shall be flush and screwdriver operated with 1 1/2" cam and lock studs, or shall be key operated cylinder lock with automatic dust shutter. Furnished with plastic grommet for studs only to protect hole made in wall board.
5. Finish shall be prime coat of rust inhibitive electrostatic powder, baked white enamel.
6. Sheet metal meets National Council of Radiation Protection #49.
7. Varying thicknesses of lead available. Custom door sizes also available.

PROJECT SCHEDULE					
Qty.	H	W	No. of Latches	Finish	Remarks

STANDARD SIZES

DOOR SIZE H X W (IN.)	WALL/CEILING OPENING (IN.)	NUMBER OF LATCHES	SHIP WT. (LBS.)
12 x 12	10 1/2 x 10 1/2	1	6.7
18 x 18	16 1/2 x 16 1/2	2	11.6
24 x 24	22 1/2 x 22 1/2	2	18.1
30 x 22	28 1/2 x 20 1/2	2	19.5

