

Location: _____



MFRU

**UNINSULATED FIRE RATED
ACCESS DOOR**

Specification: MIFAB Series MFRU uninsulated fire rated access door is approved by Underwriters Laboratories Inc., for 1 ½ hours, “B” label in walls. The door meets ANSI-UL 10B standards. It has a unique white finish.



Material: MFRU Series is 16 gage satin coat steel door and frame. The MFRUSS Stainless Steel Series is 16 gage #304 stainless steel door and frame.

Finish: Satin coat steel doors have a primed white finish. Stainless steel doors have a #4 brush satin finish.

Door: Flush to frame. Self-closing. Can be opened from the inside or back of the door with MIFAB’s unique thumb turn latch.

Frame: Four piece welded frame with masonry mounting straps.

Hinge: Concealed pivot pins.

Spring: Heavy duty.


Latch: Standard - Flush mounted, interchangeable turn ring operator and key operator latch. Optional - cylinder key lock. All of MIFAB’s cylinder key locks are keyed alike.

Fire Rating: Underwriters Laboratories “B” label. 1½ hour for walls. Insulation not required.


Packaging: Individual pack.

SUFFIX OPTIONAL VARIATIONS

-C Cylinder key lock



Key Operator



Turn Ring Operator

“B” x “A”	WALL OPENING	SHIP WEIGHT (Lbs.)	LATCHES	MILD STEEL MODEL #	STAINLESS STEEL MODEL #
8" x 8"	8-1/2" x 8-1/2"	9.0	1	MFRU0808	MFRUSS0808
10" x 10"	10-1/2" x 10-1/2"	10.0	1	MFRU1010	MFRUSS1010
12" x 12"	12-1/2" x 12-1/2"	12.5	1	MFRU1212	MFRUSS1212
12" x 18"	12-1/2" x 18-1/2"	14.5	1	MFRU1218	MFRUSS1218
12" x 24"	12-1/2" x 24-1/2"	17.0	1	MFRU1224	MFRUSS1224
14" x 14"	14-1/2" x 14-1/2"	14.0	1	MFRU1414	MFRUSS1414
16" x 16"	16-1/2" x 16-1/2"	15.0	1	MFRU1616	MFRUSS1616
18" x 18"	18-1/2" x 18-1/2"	17.0	1	MFRU1818	MFRUSS1818
20" x 20"	20-1/2" x 20-1/2"	21.5	1	MFRU2020	MFRUSS2020
22" x 22"	22-1/2" x 22-1/2"	25.0	1	MFRU2222	MFRUSS2222
22" x 30"	22-1/2" x 30-1/2"	31.5	1	MFRU2230	MFRUSS2230
24" x 24"	24-1/2" x 24-1/2"	27.0	1	MFRU2424	MFRUSS2424
24" x 36"	24-1/2" x 36-1/2"	41.5	2	MFRU2436	MFRUSS2436
24" x 48"	24-1/2" x 48-1/2"	58.5	2	MFRU2448	MFRUSS2448
30" x 30"	30-1/2" x 30-1/2"	40.5	2	MFRU3030	MFRUSS3030
32" x 32"	32-1/2" x 32-1/2"	42.5	2	MFRU3232	MFRUSS3232
36" x 36"	36-1/2" x 36-1/2"	54.0	2	MFRU3636	MFRUSS3636
36" x 48"	36-1/2" x 48-1/2"	72.5	2	MFRU3648	MFRUSS3648




California State
Fire Marshall
Approval #
3330-1535:00

A-B Door Size

C-D Overall Dimensions - Door Size - Plus 2 5/8" (67)

E Wall Opening - Door Size - Plus 1/2" (13) (Allow an extra 1/4" (6) clearance for latch housing on “D” side.)



(Dimension) Denotes Millimetres

Note: The hinge is always furnished on the “A” or height (longer) dimension, unless otherwise specified.

Job Name: _____	Page No: _____
Section No: _____	Contract: _____
Schedule No: _____	Purchase Order No: _____