



# SUBMITTAL/TECHNICAL DATA SHEET

## APPLICATION

The Halotron® I clean agent is and excellent replacement for Halon 1211 extinguishers. Because the extinguishing agent leaves no residue, it is ideal for protecting sensitive electronic equipment, laboratories, museums and vehicle maintenance facilities.

## DESCRIPTIONS

This model contains the clean extinguishing agent Halotron® 1, which is EPA-approved, government accepted and specified. This agent discharges as a liquid, then quickly evaporates, leaving no residue to clean up afterwards. U.S. FAA-approved for use in airports. NFPA-10 rating. Electrically non-conductive.

## SPECIFICATIONS

CONFORMS TO TEST STANDARDS:  
CAN/ULC-S556-ANSI/UL2129 &  
CAN/ULC-S508-ANSI/UL711

OPERATION: Squeeze the lever, which opens the valve, allowing the chemical to be forced out.

TEMPERATURE RANGE: -40° F (-40° C) to 120° F (49° C)

CONSTRUCTION: Drawn steel cylinder with steel siphon tubes, power cone discharge stream, upright squeeze grip visual pressure gauge and corrosion-resistant paint finish.

VALVE MATERIAL: Aluminum

NOMINAL CAPACITY: 20 lb

UL Rating: 2A-10BC

CLASS: A,B,C Fires

For a complete list of options visit  
[www.AccessDoorsAndPanels.com](http://www.AccessDoorsAndPanels.com)



SKU: **MERCURY**

**MERCURY EXTINGUISHERS**

HALOTRON AGENT



## DIMENSIONS AND APPEARANCE

>> CLICK TO VIEW ADDITIONAL DETAILS AND PRICING <<

### STANDARD DIMENSIONS:

Model	Type	Nominal Capacity	Ship. Weight	Cylinder Dia.	Overall Height	Overall Width	Shipping Vol	UL Rating @ 68°F	Optional Mount. Bracket
Mercury 2-1/2* (FM02C)	Halotron®	2-½ lbs.	5-¼ lbs.	3-¾"	15-½"	6-¾"	.25 cu.ft.	2B:C	MB817C*
Mercury 5 (FM05C)		5 lbs.	9-½ lbs.	4-¼"	16-¾"	7-¼"	.3 cu.ft.	5B:C	MB818C
Mercury 11 (FM11C)		11 lbs.	21-¼ lbs.	7"	17-½"	8-¾"	1.0 cu.ft.	1A-10B:C	MB810C
Mercury 11 (FM11A)		11 lbs.	22-½ lbs.	6"	21-7/8"	9-¼"	1.0 cu.ft.	1A-10B:C	MB812A
Mercury 15-1/2 (FM15C)		15-½ lbs.	25-¾ lbs.	7"	17-½"	8-¾"	1.0 cu.ft.	2A-10B:C	MB810C
Mercury 15-1/2 (FM15A)		15-½ lbs.	27-½ lbs.	6"	21-7/8"	9-¼"	1.0 cu.ft.	2A-10B:C	MB812A

\*Indicates mounting bracket standard. J hook wall bracket standard with all other extinguisher - mounting bracket available for those models at extra charge.  
- FM02C are N/A for USCG approved, rest of the products are USCG approved.

Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service for more information about ordering tagged extinguishers in your area.

### OPTIONS AT ADDITIONAL COST:

	OPTIONS	AVAILABLE MODELS
■	Brass Valve Steel Cylinder	Mercury 11, Mercury 15-1/2
■	Aluminum Valve Chrome Cylinder	Mercury 2-1/2, Mercury 5

Dimensions of extinguishers with above options may vary from table above.



**CLASS B FIRES**  
Flammable Liquids and Gases



**CLASS C FIRES**  
Energized Electrical Equipment

## PROJECT DATA

Custom Sizes Available - Fast!

Scan or Click



To view Pricing and Additional Product Info.

PROJECT NAME :	QTY	W	H	OPTIONS
ARCHITECT :				
DEALER :				
CONTRACTOR :				
LOCATION :	SPECIAL INSTRUCTIONS :			
DATE :	SUBMITTAL APPROVAL : (signature or stamp)			
TAGGING INSTRUCTIONS :				

TELEPHONE:  
1-888-457-1275  
FAX:  
1-888-626-2907



PO BOX 66738 #76520,  
SAINT LOUIS, MO  
63166-6738  
USA



WEBSITE:  
[www.AccessDoorsAndPanels.com](http://www.AccessDoorsAndPanels.com)  
E-MAIL:  
[info@AccessDoorsAndPanels.com](mailto:info@AccessDoorsAndPanels.com)