



THIS DRAWING IS THE PROPERTY OF THE BILCO COMPANY AND INCORPORATED INFORMATION HEREIN IS PROPRIETARY. PUBLICATION AND/OR PUBLIC DISTRIBUTION IN WHOLE OR IN PART IS EXPRESSLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF THE BILCO COMPANY. THE INFORMATION CONTAINED HEREIN REMAINS THE PROPERTY OF THE BILCO COMPANY. ALL RIGHTS RESERVED.

- SPECIFICATIONS**
- FRAME W/ FLASHING (CORNERS FULL WELDED)
    - 20MM - 14 GAUGE P.B. CALV. STEEL
    - 50MM - 11 GAUGE ALUMINUM
  - PINTLE HENCE
  - GASKET (ALL AROUND COVER)
  - COVER GAUGE
    - 20MM - 14 GAUGE P.B. CALV. STEEL
    - 50MM - 11 GAUGE ALUMINUM
  - COVER LINER
    - 20MM - 22 GAUGE P.B. CALV. STEEL
    - 50MM - 18 GAUGE ALUMINUM
  - LIFTING MECHANISM WITH REINFORCED COMPOSITE TUBES AND COMPRESSION SPRINGS
  - 1" RIGID FIBERGLASS INSULATION
  - SLAM LATCH
  - INSIDE AND OUTSIDE HANDLES W/ PADLOCK HASPS
  - ARM GUIDE BRACKET
  - 1" THICK FIBERGLASS COVER INSULATION
  - HOLD OPEN ARM W/ RED VINYL CRIP
  - NITROPRENE GASKET
  - LOCK STRIKE & PADLOCK HASP
  - ANCHOR TABS (QTY & LOCATION VARIES W/ SIZE)
  - GUIDE ARM (F REQ'D)
- SHOP FINISH:  
 STEEL: RED OXIDE PRIMER  
 ALUMINUM: MILL FINISH  
 HARDWARE: ZINC PLATED & CHROMATE SEATED (UNLESS OTHERWISE SPECIFIED)
- THIS PRODUCT MAY BE INSTALLED ON EITHER A FLAT OR SLOPING ROOF. WHEN INSTALLED ON A SLOPE, THE HENCE SKEE MUST RUN PARALLEL WITH THE SLOPE. IF SLOPE EXCEEDS 30°, ADVISE FACTORY FOR MODIFICATION.

**SINGLE LEAF ROOF SCUTTLE - TYPE VM**

QTY	TYPE	QTY	TYPE	SIZE
<input type="checkbox"/>				[914mm] x [762mm]
				[762mm] x [1
	L-20MM		L-50MM	