Lo	ca	tio	n



UD

DUCT ACCESS DOORS

Specification: The MIFAB UD Series of duct access doors are designed to provide access to equipment installed within ducts. The door panels are insulated and gaskets between the panel and frame will assure tight seals without obstruction in the air system.



Material: UD Series is 24 gage galvanized steel door and 24 gage galva-

nized steel frame.

Finish: Not painted. Shipped in natural galvanized steel finish. **Door:** 1" (25) thick, double wall construction and insulated.

Frame: With bend over tabs to attach to the duct.

Hinge: Continuous piano type.

Latch: Standard – Cam latch is self-tightening and hand operated.

Packaging: Individual pack

MODEL #	DOOR SIZE ("B" X "A")	SHIPPING WEIGHT (Lbs.)	LATCHES
UD0606	6" x 6"	1.50	1
UD0808	8" x 8"	2.50	1
UD1010	10" x 10"	3.00	1
UD1212	12" x 12"	4.00	1
UD1414	14" x 14"	5.00	2
UD1616	16" x 16"	7.00	2
UD1818	18" x 18"	8.00	2
UD2020	20" x 20"	11.00	2
UD2424	24" x 24"	13.00	2

Click here to Online Product Page and Pricing

AccessDoorsAndPanels

Phone: 1-800-609-2917

Fax: 1-888-626-2907

Email: info@accessdoorsandpanels.com

Website: www.AccessDoorsAndPanels.com

Address: PO Box 66738 #76520, Saint Louis, MO 63166-6738